

TECHNICAL INFORMATION

Physical Properties

Substrate Type: Non-Woven
Approximate total weight: 460g per m²

Roll Width x Length

137 cm wide x 27.4 m
54" (W) x 30 yards (L)

Pattern Repeat

Free Match

Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations (Class 1, BS 476 part 7). Euroclass B - s2, d0. Class A ASTM E-84 Tunnel Test.

Adhesive

Newmor Heavy
(Suitable for most absorbent surfaces)

Bacteria Resistance:

Manufactured to include antimicrobial protection as standard to help in the control of fungi, actinomycetes and bacteria.

Physical Properties

Conforms to requirements of BS EN 15102, BS EN 259 and Federal Specification CCC-W-408A & C CFFA Quality Standard for Vinyl Coated Fabric Wallcoverings CFFA-W-101A

Stain/Chemical Resistance:

1-12 ASTM D-1308-1987 Federal Spot Test. Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:

Manufactured to BSEN ISO9001:2008

Availability:

Every product stocked in depth.
Please allow 5/7 days for delivery

Samples:

Larger samples are readily available on request.

Washability:

Fully Washable* and durable

Impact Resistance

Pass

*Washable. Our products can be washed and in many cases scrubbed repeatedly to remove any marks, without damaging the product itself.



British Product | Global Support