

TECHNICAL INFORMATION

Physical Properties

Substrate Type: Non-Woven
Approximate total weight: 460g per m²

Roll Width x Length

137 cm wide x 27.4 m
54" (W) x 30 yards (L)

Pattern Repeat

Free Match

Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations (Class 1, BS476 Part 7). Euroclass B - s2, d0. Class A ASTM E-84 Tunnel Test.

Adhesive

Newmor Heavy
(Suitable for most absorbent surfaces)

Bacteria Resistance:

Manufactured to include antimicrobial protection as standard to help in the control of fungi, actinomycetes and bacteria.

Physical Properties

Conforms to BSEN15102:2007, BSEN259 and Federal Specification on CCC-W-408A & C CFFA Quality Standard for Vinyl Coated Fabric Wallcoverings CFFA-W-101A

Stain/Chemical Resistance:

1-12 ASTM D-1308-1987 Federal Spot Test.
Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:

Manufactured to BSEN ISO9001:2008

Availability:

Every product stocked in depth.
Please allow 5/7 days for delivery

Samples:

Larger samples are readily available on request.

Washability:

Fully Washable* and durable

Impact Resistance

Pass

*Washable. Our products can be washed and in many cases scrubbed repeatedly to remove any marks, without damaging the product itself.

