TECHNICAL INFORMATION

Physical properties
Total weight: 400g/m² (nominal)
Vinyl Weight: 310g/m² (nominal)
Substrate Type: Non-Woven Fabric
Substrate weight: 90g/m² (nominal)

Type II and other specifications available

Tensile Strength:	MD 40 N/cm (nominal)
	TD 30 N/cm (nominal
Tear Strength:	4500 mN (nominal)

Roll size:
130cm x 30m – cut lengths available

Pattern Repeat:
Vertical: Free Match
Horizontal: None

Fire Rating:
Class 'O" to the requirements of Approved Document B of the British Building Regulations (Class 1, BS 476 part 7).
Euroclass B - s2, d0. Class A ASTM E-84 Tunnel Test.

Adhesive:
Fabric backed vinyls - Newmor Heavy.
Varies with substrate - please enquire.

Bacteria Resistance:
Contains an active Fungicide.

Light Fast:
Excellent Light Fastness
BS EN ISO 105-B02 7/8

LRV = Light reflective value

Specifications
Conforms to requirements of BS EN 15102, BS EN 259 and Federal Specification CCC-W-408A & C CFFA Quality Standard for Vinyl Coated Fabric Wallcoverings CFFA-W-101A

Stain/Chemical Resistance:
Pass ASTM D-1308-1987 Federal Spot Test. Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:
All management systems and production procedures comply with ISO 9001, the internationally recognised Quality Standard.

Availability:
Every product stocked in depth.
5.00pm deadline for next day delivery (UK only).

Origin:
Designed, coloured, manufactured and stocked in the UK.

Warranty:
Newmor offers a five year warranty against manufacturing defects.
Full details available on application.

Samples:
Larger samples are readily available on request.

Maintenance:
Fully washable and in most cases products can be scrubbed repeatedly to remove any marks without damaging the product itself. Most products are also able to withstand the use of chlorine cleaning agents.

FM23833 BCFA member INTERNATIONAL MARITIME ORGANIZATION British Product | Global Support

Newmor WALLCOVERINGS

UK SALES:
T: 01938 551990
E: sales@newmor.com

EXPORT SALES:
T: + 44 (0) 1938 55 2671
E: enquirires@newmor.com